



The Completely concealed and 3D adjustable Hinge

Exclusively distributed by:



Visit our show room:

Unit 1202 Atlanta Centre, 31 Annapolis St., Greenhills San Juan, Philippines 1502 Tel: (632) 722 6671 / 722 6664 Fax: (632) 722 4933 marketing@trendbuilding.com www.trendbuilding.com

TFCTUS®

Clean design, high load capacity, secure assembly and multifaceted scope of application for high quality residential and commercial doors.

TE 340 3D

for flush residential and commercial doors

Hinge	up to 80 kg (1/6 lbs)
Technical data	
Load capacity	80 kg (176 lbs)

Length (door/frame) 160/160 mm (6.299/6.299 ")
Width (door/frame) 28/28 mm (1.102/1.102")

TE 540 3D

Router bit diameter

for flush commercial doors

Hinge

Technical data

 Load capacity
 120 kg (264 lbs)

 Length (door/frame)
 200/200 mm (7.874/7.874 ")

 Width (door/frame)
 32/32 mm (1.260/1.260 ")

Router bit diameter 24 mm (0.945 ")

TE 640 3D

for flush high performance commercial doors

Hinge	up to 200 kg (440 lbs)
W-1100000000000000000000000000000000000	

Technical data Load capacity

200 kg (440 lbs)

24 mm (0.945")

up to 120 kg (264 lbs)

Length (door/frame)

Width (door/frame)

Router bit diameter

240/240 mm (9.449/9.449 ") 32/32 mm (1.260/1.260 ") 24 mm (0.945 ")

ADJUSTMENT - Tectus Series

Three way adjustable

 Side
 +/-3 mm (0.118 ")

 Height
 +/-3 mm (0.118 ")

 Depth
 +/-1 mm (0.039 ")

рериі 177- Гінші (0.039)

Side adjustment depth adjustment depth adjustment depth adjustment depth adjustment Clamping screws Height adjustment of a opening needs. The TECTUS hinge offers a

TECTUS® – In 2003, SIMONSWERK introduced an innovative concealed hinge, TECTUS, which allows the adjustment of a door in three dimensions. This series features an entire range for your architectural opening needs. The TECTUS hinge offers a "clean" look, which has not been matched by any other manufacturer.













